

XPZ-3VX

Beschreibung	Richtlänge	Bezugslänge	Vorrat/Bestand	Neu
	mm	Zoll		
XPZ562/3VX223	562	22,3	•	•
XPZ587/3VX233	587	23,3	•	
XPZ600/3VX238	600	23,8	•	
XPZ612/3VX243	612	24,3	•	
XPZ630/3VX250	630	25,0	•	
XPZ637/3VX252	637	25,2	•	
XPZ660/3VX261	660	26,1	•	•
XPZ662/3VX262	662	26,2	•	
XPZ670/3VX265	670	26,5	•	
XPZ687/3VX272	687	27,2	•	
XPZ710/3VX280	710	28,0	•	
XPZ722/3VX286	722	28,6	•	
XPZ730/3VX289	730	28,9	•	
XPZ737/3VX292	737	29,2	•	
XPZ750/3VX297	750	29,7	•	
XPZ762/3VX300	762	30,0	•	
XPZ772/3VX305	772	30,5	•	
XPZ775/3VX307	775	30,7	•	•
XPZ787/3VX311	787	31,1	•	
XPZ800/3VX315	800	31,5	•	
XPZ812/3VX321	812	32,1	•	
XPZ817/3VX323	817	32,3	•	•
XPZ825/3VX325	825	32,5	•	•
XPZ837/3VX331	837	33,1	•	
XPZ850/3VX335	850	33,5	•	
XPZ862/3VX341	862	34,1	•	
XPZ875/3VX346	875	34,6	•	
XPZ887/3VX350	887	35,0	•	
XPZ900/3VX355	900	35,5	•	
XPZ912/3VX360	912	36,0	•	
XPZ917/3VX362	917	36,2	•	•
XPZ925/3VX366	925	36,6	•	
XPZ937/3VX370	937	37,0	•	
XPZ950/3VX375	950	37,5	•	
XPZ962/3VX380	962	38,0	•	
XPZ975/3VX385	975	38,5	•	
XPZ980/3VX387	980	38,7	•	
XPZ987/3VX390	987	39,0	•	
XPZ1000/3VX395	1000	39,5	•	
XPZ1012/3VX400	1012	40,0	•	
XPZ1025/3VX405	1025	40,5	•	•
XPZ1030/3VX407	1030	40,7	•	
XPZ1037/3VX410	1037	41,0	•	
XPZ1047/3VX414	1047	41,4	•	•
XPZ1060/3VX420	1060	42,0	•	•
XPZ1077/3VX425	1077	42,5	•	•
XPZ1080/3VX426	1080	42,6	•	
XPZ1087/3VX429	1087	42,9	•	
XPZ1110/3VX438	1110	43,8	•	•
XPZ1112/3VX439	1112	43,9	•	
XPZ1120/3VX442	1120	44,2	•	

XPZ-3VX (FORTS.)

Beschreibung	Richtlänge	Bezugslänge	Vorrat/Bestand	Neu
	mm	Zoll		
XPZ1137/3VX450	1137	45,0	•	•
XPZ1140/3VX450	1140	45,0	•	
XPZ1150/3VX454	1150	45,4	•	
XPZ1162/3VX459	1162	45,9	•	•
XPZ1180/3VX464	1180	46,4	•	
XPZ1187/3VX469	1187	46,9	•	
XPZ1202/3VX475	1202	47,5	•	
XPZ1212/3VX479	1212	47,9	•	
XPZ1220/3VX482	1220	48,2	•	•
XPZ1237/3VX487	1237	48,7	•	
XPZ1250/3VX494	1250	49,4	•	
XPZ1262/3VX500	1262	50,0	•	
XPZ1270/3VX502	1270	50,2	•	
XPZ1280/3VX505	1280	50,5	•	
XPZ1287/3VX508	1287	50,8	•	
XPZ1312/3VX518	1312	51,8	•	
XPZ1320/3VX520	1320	52,0	•	
XPZ1337/3VX530	1337	53,0	•	
XPZ1347/3VX532	1347	53,2	•	•
XPZ1360/3VX537	1360	53,7	•	•
XPZ1362/3VX538	1362	53,8	•	
XPZ1387/3VX548	1387	54,8	•	•
XPZ1400/3VX553	1400	55,3	•	
XPZ1412/3VX560	1412	56,0	•	•
XPZ1420/3VX563	1420	56,3	•	
XPZ1437/3VX567	1437	56,7	•	
XPZ1450/3VX572	1450	57,2	•	
XPZ1462/3VX578	1462	57,8	•	•
XPZ1487/3VX587	1487	58,7	•	
XPZ1500/3VX590	1500	59,0	•	•
XPZ1512/3VX600	1512	60,0	•	•
XPZ1520/3VX603	1520	60,3	•	
XPZ1537/3VX607	1537	60,7	•	
XPZ1550/3VX612	1550	61,2	•	
XPZ1562/3VX617	1562	61,7	•	•
XPZ1587/3VX626	1587	62,6	•	
XPZ1600/3VX630	1600	63,0	•	
XPZ1612/3VX637	1612	63,7	•	•
XPZ1637/3VX646	1637	64,6	•	•
XPZ1650/3VX650	1650	65,0	•	
XPZ1662/3VX656	1662	65,6	•	•
XPZ1687/3VX666	1687	66,6	•	
XPZ1700/3VX670	1700	67,0	•	
XPZ1737/3VX686	1737	68,6	•	•
XPZ1750/3VX690	1750	69,0	•	
XPZ1762/3VX696	1762	69,6	•	•
XPZ1787/3VX705	1787	70,5	•	•
XPZ1800/3VX710	1800	71,0	•	
XPZ1812/3VX715	1812	71,5	•	•
XPZ1837/3VX725	1837	72,5	•	•
XPZ1850/3VX730	1850	73,0	•	

XPZ-3VX (FORTS.)

Beschreibung	Richtlänge	Bezugslänge	Vorrat/Bestand	Neu
	mm	Zoll		
XPZ1862/3VX735	1862	73,5	•	•
XPZ1887/3VX745	1887	74,5	•	•
XPZ1900/3VX750	1900	75,0	•	
XPZ1937/3VX765	1937	76,5	•	•
XPZ1950/3VX771	1950	77,1	•	
XPZ1987/3VX784	1987	78,4	•	•
XPZ2000/3VX790	2000	79,0	•	
XPZ2030/3VX800	2030	80,0	•	
XPZ2037/3VX804	2037	80,4	•	•
XPZ2060/3VX813	2060	81,3	•	•
XPZ2120/3VX836	2120	83,6	•	
XPZ2137/3VX843	2137	84,3	•	•
XPZ2160/3VX850	2160	85,0	•	
XPZ2187/3VX863	2187	86,3	•	•
XPZ2240/3VX883	2240	88,3	•	
XPZ2262/3VX892	2262	89,2	•	•
XPZ2280/3VX900	2280	90,0	•	
XPZ2287/3VX902	2287	90,2	•	•
XPZ2360/3VX931	2360	93,1	•	
XPZ2410/3VX950	2410	95,0	•	
XPZ2430/3VX959	2430	95,9	•	•
XPZ2500/3VX986	2500	98,6	•	
XPZ2540/3VX1000	2540	100,0	•	
XPZ2650/3VX1045	2650	104,5	•	
XPZ2690/3VX1060	2690	106,0	•	
XPZ2800/3VX1104	2800	110,4	•	
XPZ2840/3VX1120	2840	112,0	•	
XPZ3000/3VX1180	3000	118,0	•	
XPZ3150/3VX1242	3150	124,2	•	
XPZ3350/3VX1320	3350	132,0	•	
XPZ3550/3VX1400	3550	140,0	•	

XPA

Beschreibung	Richtlänge	Vorrat/Bestand	Neu
mm			
XPA690	690	•	
XPA732	732	•	
XPA747	747	•	
XPA750	750	•	•
XPA757	757	•	
XPA775	775	•	•
XPA782	782	•	
XPA800	800	•	
XPA807	807	•	•
XPA825	825	•	•
XPA832	832	•	
XPA850	850	•	
XPA857	857	•	
XPA875	875	•	•
XPA882	882	•	
XPA900	900	•	
XPA907	907	•	
XPA925	925	•	
XPA932	932	•	
XPA950	950	•	
XPA957	957	•	
XPA975	975	•	
XPA982	982	•	
XPA1000	1000	•	
XPA1007	1007	•	
XPA1030	1030	•	
XPA1060	1060	•	
XPA1069	1069	•	
XPA1082	1082	•	
XPA1090	1090	•	
XPA1107	1107	•	
XPA1120	1120	•	
XPA1132	1132	•	•
XPA1140	1140	•	
XPA1142	1142	•	•
XPA1150	1150	•	
XPA1157	1157	•	
XPA1172	1172	•	•
XPA1180	1180	•	
XPA1207	1207	•	
XPA1215	1215	•	
XPA1220	1220	•	•
XPA1232	1232	•	
XPA1250	1250	•	
XPA1257	1257	•	
XPA1272	1272	•	•
XPA1282	1282	•	
XPA1285	1285	•	
XPA1307	1307	•	
XPA1320	1320	•	
XPA1332	1332	•	

XPA (FORTS.)

Beschreibung	Richtlänge	Vorrat/Bestand	Neu
	mm		
XPA1357	1357	•	
XPA1360	1360	•	
XPA1367	1367	•	
XPA1382	1382	•	
XPA1400	1400	•	
XPA1407	1407	•	•
XPA1432	1432	•	•
XPA1442	1442	•	•
XPA1450	1450	•	
XPA1457	1457	•	
XPA1462	1462	•	•
XPA1482	1482	•	
XPA1500	1500	•	
XPA1507	1507	•	
XPA1522	1522	•	•
XPA1532	1532	•	
XPA1550	1550	•	
XPA1557	1557	•	•
XPA1582	1582	•	
XPA1600	1600	•	
XPA1607	1607	•	•
XPA1632	1632	•	
XPA1650	1650	•	
XPA1657	1657	•	
XPA1680	1680	•	
XPA1682	1682	•	•
XPA1700	1700	•	
XPA1707	1707	•	•
XPA1732	1732	•	
XPA1750	1750	•	
XPA1757	1757	•	•
XPA1782	1782	•	
XPA1800	1800	•	
XPA1807	1807	•	•
XPA1832	1832	•	•
XPA1850	1850	•	
XPA1857	1857	•	•
XPA1882	1882	•	•
XPA1900	1900	•	
XPA1907	1907	•	•
XPA1932	1932	•	•
XPA1950	1950	•	
XPA1957	1957	•	•
XPA1982	1982	•	•
XPA2000	2000	•	
XPA2032	2032	•	•
XPA2057	2057	•	•
XPA2060	2060	•	
XPA2082	2082	•	•
XPA2120	2120	•	
XPA2132	2132	•	•

02 QUAD-POWER™ 4

FLANKENOFFENER, FORMVERZAHNTER HOCHLEISTUNGS-SCHMALKEILRIEMEN



XPA (FORTS.)

Beschreibung	Richtlänge	Vorrat/Bestand	Neu
	mm		
XPA2180	2180	•	
XPA2207	2207	•	•
XPA2232	2232	•	•
XPA2240	2240	•	
XPA2282	2282	•	•
XPA2300	2300	•	•
XPA2307	2307	•	•
XPA2332	2332	•	•
XPA2360	2360	•	
XPA2382	2382	•	•
XPA2430	2430	•	
XPA2482	2482	•	•
XPA2500	2500	•	
XPA2532	2532	•	•
XPA2582	2582	•	•
XPA2607	2607	•	•
XPA2632	2632	•	•
XPA2650	2650	•	
XPA2682	2682	•	•
XPA2732	2732	•	•
XPA2782	2782	•	•
XPA2800	2800	•	
XPA2832	2832	•	•
XPA2847	2847	•	•
XPA2882	2882	•	•
XPA2900	2900	•	•
XPA2932	2932	•	•
XPA2982	2982	•	•
XPA3000	3000	•	
XPA3150	3150	•	
XPA3350	3350	•	
XPA3550	3550	•	
XPA3750	3750	•	
XPA4000	4000	•	

XPB-5VX

Beschreibung	Richtlänge	Bezugslänge	Vorrat/Bestand	Neu
	mm	Zoll		
XPB1000/5VX398	1000	39,8	●	
XPB1060/5VX422	1060	42,2	●	
XPB1080/5VX430	1080	43,0	●	
XPB1120/5VX445	1120	44,5	●	
XPB1180/5VX470	1180	47,0	●	
XPB1250/5VX497	1250	49,7	●	
XPB1260/5VX500	1260	50,0	●	
XPB1280/5VX510	1280	51,0	●	●
XPB1320/5VX524	1320	52,4	●	
XPB1340/5VX530	1340	53,0	●	
XPB1400/5VX556	1400	55,6	●	
XPB1410/5VX560	1410	56,0	●	
XPB1450/5VX575	1450	57,5	●	
XPB1500/5VX595	1500	59,5	●	
XPB1510/5VX600	1510	60,0	●	
XPB1550/5VX615	1550	61,5	●	
XPB1590/5VX630	1590	63,0	●	
XPB1600/5VX634	1600	63,4	●	
XPB1650/5VX654	1650	65,4	●	
XPB1690/5VX670	1690	67,0	●	
XPB1700/5VX674	1700	67,4	●	
XPB1750/5VX693	1750	69,3	●	
XPB1800/5VX713	1800	71,3	●	
XPB1850/5VX733	1850	73,3	●	
XPB1900/5VX750	1900	75,0	●	●
XPB1950/5VX772	1950	77,2	●	
XPB2000/5VX790	2000	79,0	●	
XPB2020/5VX800	2020	80,0	●	
XPB2120/5VX840	2120	84,0	●	
XPB2150/5VX850	2150	85,0	●	
XPB2186/5VX860	2186	86,0	●	
XPB2240/5VX886	2240	88,6	●	
XPB2280/5VX900	2280	90,0	●	
XPB2300/5VX910	2300	91,0	●	
XPB2360/5VX934	2360	93,4	●	
XPB2410/5VX953	2410	95,3	●	
XPB2433/5VX960	2433	96,0	●	
XPB2500/5VX990	2500	99,0	●	
XPB2530/5VX1000	2530	100,0	●	
XPB2650/5VX1050	2650	105,0	●	
XPB2680/5VX1060	2680	106,0	●	
XPB2800/5VX1108	2800	110,8	●	
XPB2840/5VX1120	2840	112,0	●	●
XPB2900/5VX1146	2900	114,6	●	
XPB2990/5VX1180	2990	118,0	●	
XPB3000/5VX1186	3000	118,6	●	
XPB3150/5VX1245	3150	124,5	●	
XPB3160/5VX1250	3160	125,0	●	
XPB3320/5VX1312	3320	131,2	●	
XPB3350/5VX1320	3350	132,0	●	●
XPB3440/5VX1359	3440	135,9	●	

02 QUAD-POWER™ 4

FLANKENOFFENER, FORMVERZAHNTER HOCHLEISTUNGS-SCHMALKEILRIEMEN



XPB-5VX (FORTS.)

Beschreibung	Richtlänge	Bezugslänge	Vorrat/Bestand	Neu
	mm	Zoll		
XPB3550/5VX1400	3550	140,0	●	
XPB3750/5VX1481	3750	148,1	●	
XPB3800/5VX1500	3800	150,0	●	
XPB4000/5VX1579	4000	157,9	●	
XPB4053/5VX1600	4053	160,0	●	
XPB4250/5VX1678	4250	167,8	●	
XPB4307/5VX1700	4307	170,0	●	
XPB4500/5VX1776	4500	177,6	●	
XPB4560/5VX1800	4560	180,0	●	
XPB4750/5VX1875	4750	187,5	●	
XPB4815/5VX1900	4815	190,0	●	
XPB5000/5VX1973	5000	197,3	●	
XPB5070/5VX2000	5070	200,0	●	

XPC

Beschreibung	Richtlänge	Vorrat/Bestand	Neu
	mm		
XPC1900	1900	●	
XPC2000	2000	●	
XPC2120	2120	●	
XPC2240	2240	●	
XPC2360	2360	●	
XPC2500	2500	●	
XPC2650	2650	●	
XPC2800	2800	●	
XPC3000	3000	●	
XPC3150	3150	●	
XPC3350	3350	●	
XPC3550	3550	●	
XPC3750	3750	●	
XPC4000	4000	●	
XPC4250	4250	●	
XPC4500	4500	●	
XPC4750	4750	●	
XPC5000	5000	●	