

	1008	1108	1210	1610	1615	2012	2517	3020	3030	3525	3535	4030	4040	4535	4545	5040	5050
TB mit metrischer Bohrung, nach DIN 6885 Teil 1																	
Bohrungs- durchmesser d ₂ (mm)				14	14	14	16			35		40					
				15	16	15	18			38		42					
				16	18	16	19	25		40	35	45	40	55		70	70
	10	10	11	15	16	18	20	28		42	38	48	42	60	55	75	75
	11	12	14	16	18	19	22	30	35	45	40	50	45	65	60	80	80
	12	14	15	18	19	20	25	32	40	48	42	55	48	70	65	85	85
	14	15	16	20	20	22	28	38	42	50	45	60	50	75	70	85	85
	15	16	18	22	22	24	30	40	45	55	50	65	55	80	75	90	90
	16	17	19	24	24	25	32	42	48	55	50	70	60	85	80	95	95
	18	18	20	25	25	28	35	45	50	60	55	75	65	90	85	100	100
	19	19	22	28	28	30	38	55	60	65	60	80	70	95	90	105	105
	20	20	24	30	30	32	40	50	60	70	65	85	75	100	95	110	110
	22	22	25	32	32	35	42	55	65	75	70	90	80	105	100	115	115
	24▲	24	28	35	35	38	45	60	70	85	80	95	85	110	105	120	120
	25▲	25	30	38	38	40	48	65	75	90	85	100	90	115	110	125	125
		28▲	32	40	42	50	70		95	85	105	95	120				
			42▲	45	48	55	75		100▲	90	110	100	125				
				48	50	60	65▲										
Innensech- kantschrauben Hexagon (Zoll)	1/4 x 1/2	1/4 x 1/2	3/8 x 5/8	3/8 x 5/8	3/8 x 5/8	7/16 x 7/8	1/2 x 1	5/8 x 1 1/4	5/8 x 1 1/4	1/2 x 1 1/2	1/2 x 1 1/2	5/8 x 1 3/4	5/8 x 1 3/4	3/4 x 2	3/4 x 2	7/8 x 2 1/4	7/8 x 2 1/4
Buchsenlänge (mm)	22	22	25	25	38	32	45	51	76	64	89	76	102	89	114	102	127
Gewicht bei d _{2min} (kg)	0,12	0,16	0,28	0,41	0,60	0,75	1,06	2,50	3,75	3,90	5,13	5,76	7,68	11,00	12,70	12,14	15,17

Flachnute für Taper-Buchsen					
Bohrungsdurchmesser d ₂ (mm)	Nutbreite b (mm)	Nuttiefe t ₂ (mm) min.	Bohrungsdurchmesser d ₂ (mm)	Nutbreite b (mm)	Nuttiefe t ₂ (mm) min.
24	8	2,0	65	18	2,3
25	8	1,3	100	28	4,4
28	8	2,0	115	32	5,4
42	12	2,2			

▲ Diese Bohrung ist mit Flachnut ausgeführt.

	1008	1108	1210	1610	1615	2012	2517	3020	3030	3525	3535	4040	4545	5050
TB mit Zoll-Bohrung nach Britischem Standard BS 46 Teil 1*														
Bohrungsdurchmesser d ₂ (Zoll)	3/8 1/2 5/8 3/4 7/8 1▲	3/8 1/2 5/8 3/4 7/8 1 1 1/8▲	1/2 5/8 3/4 7/8 1 1 1/8 1 1/4 1 3/8 1 1/2 1 5/8	1/2 5/8 3/4 7/8 1 1 1/8 1 1/4 1 3/8 1 1/2 1 5/8	1/2 5/8 3/4 7/8 1 1 1/8 1 1/4 1 3/8 1 1/2 1 5/8	5/8 3/4 7/8 1 1 1/8 1 1/4 1 3/8 1 1/2 1 5/8	3/4 7/8 1 1 1/8 1 1/4 1 1/2 1 3/4 1 5/8 2 2 1/8 2 1/4 2 3/8 2 1/2	1 1/4 1 3/8 1 1/2 1 5/8 1 3/4 2 2 1/8 2 1/4 2 3/8 2 1/2 2 5/8 2 3/4 2 7/8 3	1 1/4 1 3/8 1 1/2 1 5/8 1 3/4 2 2 1/8 2 1/4 2 3/8 2 1/2 2 5/8 2 3/4 2 7/8 3	1 1/2 1 5/8 1 3/4 1 7/8 2 2 1/8 2 1/4 2 3/8 2 1/2 2 5/8 2 3/4 2 7/8 3 3 1/8 3 1/4 3 3/8 3 1/2▲	1 1/2 1 5/8 1 3/4 1 7/8 2 2 1/8 2 1/4 2 3/8 2 1/2 2 5/8 2 3/4 2 7/8 3 3 1/8 3 1/4 3 3/8 3 1/2▲	1 3/4 1 7/8 2 2 1/8 2 1/4 2 3/8 2 1/2 2 5/8 2 3/4 2 7/8 3 3 1/8 3 1/4 3 3/8 3 3/4▲	2 1/4 2 3/8 2 1/2 2 3/4 2 7/8 3 3 1/2 3 3/4 4 4 1/4 4 1/2 4 3/4 5▲	3 3 1/4 3 1/2 3 3/4 4 4 1/4 4 1/2 4 3/4 5▲
Innensechskantschrauben Hexagon (Zoll)	1/4 x 1/2	1/4 x 1/2	3/8 x 5/8	3/8 x 5/8	3/8 x 5/8	7/16 x 7/8	1/2 x 1	5/8 x 1 1/4	5/8 x 1 1/4	1/2 x 1 1/2	1/2 x 1 1/2	5/8 x 1 1/4	3/4 x 2	7/8 x 2 1/4
Buchsenlänge (mm)	22	22	25	25	38	32	45	51	76	64	89	102	114	127
Gewicht bei d _{2min} (kg)	0,12	0,16	0,28	0,41	0,60	0,75	1,06	2,50	3,75	3,90	5,13	7,68	12,70	15,17

* Keine Lagerware ▲ Diese Bohrung ist mit Flachnut ausgeführt.