




Ausf. 3WF




Ausf. 4F




Ausf. 5F




Ausf. 5WF



Ausf. 7A



Ausf. 9A



Ausf. 9WF

Bezeichnung	Anzahl der Zähne	Ausführung	Material	D _p (mm)	D _e (mm)	D _t (mm)	F (mm)	S (mm)	R (mm)	D _m (mm)	D _i (mm)	Taperbuchse	Gewicht ohne Buchse (≈kg)
H - Teilung 12,7 mm für Riemenbreite 100													
TB 16 H 100	16	5F	ST	64,68	63,31	70	31	22	9	-	45	1108	0,400
TB 18 H 100	18	5F	ST	72,77	71,39	79	31	25	6	-	52	1210	0,500
TB 19 H 100	19	5F	ST	76,81	75,44	82,5	31	25	6	-	56	1210	0,600
TB 20 H 100	20	5F	ST	80,55	79,48	87	31	25	6	-	60	1210	0,700
TB 21 H 100	21	5F	ST	84,89	83,52	91	32	25	7	-	64	1210	0,800
TB 22 H 100	22	5F	ST	88,94	87,56	94	32	25	7	-	67	1210	0,900
TB 23 H 100	23	5F	ST	92,98	91,61	97	32	25	7	-	70	1610	0,900
TB 24 H 100	24	5F	ST	97,02	95,65	102	32	25	7	-	74	1610	1,000
TB 25 H 100	25	5F	ST	101,06	99,69	106	32	25	7	-	77	1610	1,000
TB 26 H 100	26	5F	ST	105,11	103,73	112	32	25	7	-	82	1610	1,200
TB 27 H 100	27	5F	ST	109,15	107,78	115	32	25	7	-	85	1610	1,300
TB 28 H 100	28	5F	ST	113,19	111,82	119,0	32	25	7	-	90	1610	1,500
TB 30 H 100	30	5F	ST	121,28	119,90	127,0	32	25	7	-	98	1610	1,700
TB 32 H 100	32	5WF	ST	129,36	127,99	135,0	32	25	7	80	106	1610	2,000
TB 36 H 100	36	5WF	ST	145,53	144,16	152,0	32	25	7	92	121	1610	2,700
TB 40 H 100	40	5WF	ST	161,70	160,33	168,0	32	25	7	92	138	1610	3,600
TB 44 H 100	44	3WF	ST	177,87	176,50	184,0	32	32	-	106	152	2012	3,800
TB 48 H 100	48	3WF	ST	194,04	192,67	200,0	32	32	-	106	169	2012	3,200
TB 60 H 100	60	9A	GG	242,55	241,18	-	34	32	1	92	223	2012	4,800
TB 72 H 100	72	9A	GG	291,06	289,69	-	34	32	1	92	270	2012	5,700
TB 84 H 100*	84	9A	GG	339,57	338,20	-	34	32	1	92	318	2012	6,800
TB 96 H 100*	96	7A	GG	388,08	386,71	-	34	45	5,5	106	366	2517	8,200
TB 120 H 100*	120	7A	GG	485,10	483,73	-	34	45	5,5	106	462	2517	12,100
H - Teilung 12,7 mm für Riemenbreite 150													
TB 18 H 150	18	5F	ST	72,77	71,39	79	45	25	20	-	-	1210	0,600
TB 19 H 150	19	5F	ST	76,81	75,44	82,5	45	25	20	-	-	1210	0,700
TB 20 H 150	20	5F	ST	80,55	79,48	87	45	25	20	-	-	1210	0,800
TB 21 H 150	21	5F	ST	84,89	83,52	91	45	25	20	-	-	1210	1,000
TB 22 H 150	22	5F	ST	88,94	87,56	94	45	25	20	-	-	1210	1,200
TB 23 H 150	23	5F	ST	92,98	91,61	97	45	25	20	-	-	1610	1,300
TB 24 H 150	24	5F	ST	97,02	95,65	102	45	25	20	-	-	1610	1,200
TB 25 H 150	25	5F	ST	101,06	99,69	106	45	25	20	-	-	1610	1,200
TB 26 H 150	26	5F	ST	105,11	103,73	112	45	25	20	-	-	1610	1,400
TB 27 H 150	27	5F	ST	109,15	107,78	115	45	25	20	-	-	1610	1,600
TB 28 H 150	28	5F	ST	113,19	111,82	120	45	25	20	-	-	1610	1,800
TB 30 H 150	30	5F	ST	121,28	119,90	128	45	25	20	-	-	1610	2,000
TB 32 H 150	32	5WF	ST	129,36	127,99	135	45	25	20	80	-	1610	2,300
TB 36 H 150	36	5WF	ST	145,53	144,16	150	45	25	20	92	118	1610	3,100
TB 40 H 150	40	5WF	ST	161,70	160,33	168	45	25	20	92	134	1610	4,000
TB 44 H 150	44	5WF	ST	177,87	176,50	184	45	32	13	106	150	2012	4,400
TB 48 H 150	48	5WF	ST	194,04	192,67	200	45	32	13	106	166	2012	4,800
TB 60 H 150	60	9A	GG	242,55	241,18	-	46	32	7,5	92	215	2517	5,400
TB 72 H 150	72	9A	GG	291,06	289,69	-	46	32	7,5	92	263	2517	6,500

Bezeichnung	Anzahl der Zähne	Ausführung	Material	D _p (mm)	D _e (mm)	D _i (mm)	F (mm)	S (mm)	R (mm)	D _m (mm)	D _i (mm)	Taper-buchse	Gewicht ohne Buchse (≈kg)
TB 84 H 150*	84	9A	GG	339,57	338,20	-	46	32	7,5	92	318	2012	8,400
TB 96 H 150*	96	9A	GG	388,08	386,71	-	46	45	0,5	106	366	2517	11,000
TB 120 H 150*	120	9A	GG	485,10	483,73	-	46	45	0,5	106	462	2517	14,800
H - Teilung 12,7 mm für Riemenbreite 200													
TB 18 H 200	18	5F	ST	72,77	71,39	79	58	25	33	-	52	1210	0,800
TB 19 H 200	19	5F	ST	76,81	75,44	82,5	58	25	33	-	56	1610	0,900
TB 20 H 200	20	5F	ST	80,85	79,48	87	58	25	33	-	60	1610	1,000
TB 21 H 200	21	5F	ST	84,89	83,52	91	58	25	33	-	64	1610	1,700
TB 22 H 200	22	5F	ST	88,94	87,56	94	58	25	33	-	67	1610	1,500
TB 23 H 200	23	5F	ST	92,98	91,61	97	58	25	33	-	70	1610	1,800
TB 24 H 200	24	5F	ST	97,02	95,65	102	58	25	33	-	74	1610	1,500
TB 25 H 200	25	5F	ST	101,06	99,69	106	58	25	33	-	77	1610	1,500
TB 26 H 200	26	5F	ST	105,11	103,73	112	58	25	33	-	82	1610	1,800
TB 27 H 200	27	5F	ST	109,15	107,78	115	58	25	33	-	85	1610	1,900
TB 28 H 200	28	5F	ST	113,19	111,82	120	58	25	33	-	90	1610	1,900
TB 30 H 200	30	5F	ST	121,28	119,90	128	58	25	33	-	98	1610	2,300
TB 32 H 200	32	5F	ST	129,36	127,99	135	58	32	26	-	106	2012	3,000
TB 36 H 200	36	5WF	ST	145,53	144,16	150	58	32	26	80	121	2012	3,000
TB 40 H 200	40	5WF	ST	161,70	160,33	168	58	32	26	80	138	2012	3,600
TB 44 H 200	44	5WF	ST	177,87	176,50	184	58	32	26	80	152	2012	4,500
TB 48 H 200	48	5WF	ST	194,04	192,67	200	58	45	13	90	169	2517	4,600
TB 60 H 200	60	9A	GG	242,55	241,18	-	60	45	7,5	90	223	2517	7,000
TB 72 H 200	72	9A	GG	291,06	289,69	-	60	45	7,5	100	270	2517	8,000
TB 84 H 200*	84	9A	GG	339,57	338,20	-	60	45	7,5	100	318	2517	9,000
TB 96 H 200*	96	9A	GG	388,08	386,71	-	60	45	7,5	120	366	2517	11,500
TB 120 H 200*	120	9A	GG	485,10	483,73	-	60	45	7,5	120	462	2517	15,400
H - Teilung 12,7 mm für Riemenbreite 300													
TB 20 H 300	20	4F	ST	80,85	79,48	87	84	38	23	-	60	1615	1,500
TB 21 H 300	21	4F	ST	84,89	83,52	91	84	38	23	-	64	1615	1,200
TB 22 H 300	22	4F	ST	88,94	87,56	94	84	38	23	-	67	1615	1,600
TB 23 H 300	23	4F	ST	92,98	91,61	97	84	38	23	-	70	1615	1,800
TB 24 H 300	24	4F	ST	97,02	95,65	102	84	38	23	-	74	1615	2,100
TB 25 H 300	25	4F	ST	101,06	99,69	106	84	38	23	-	77	1615	2,000
TB 26 H 300	26	4F	ST	105,11	103,73	112	84	38	23	-	82	1615	2,700
TB 27 H 300	27	4F	ST	109,15	107,78	115	84	32	26	-	85	2012	3,000
TB 28 H 300	28	4F	ST	113,19	111,82	120	84	32	26	-	90	2012	2,400
TB 30 H 300	30	4F	ST	121,28	119,90	128	84	32	26	-	98	2012	2,900
TB 32 H 300	32	4F	ST	129,36	127,99	135	84	45	19,5	-	106	2517	3,300
TB 36 H 300	36	4F	ST	145,53	144,16	150	84	45	19,5	-	121	2517	4,500
TB 40 H 300	40	4F	ST	161,70	160,33	168	84	45	19,5	-	138	2517	6,000
TB 44 H 300	44	9WF	ST	177,87	176,50	184	86	45	20,5	-	152	2517	6,600
TB 48 H 300	48	9WF	ST	194,04	192,67	200	86	45	20,5	119	169	2517	7,600
TB 60 H 300	60	9A	GG	242,55	241,18	-	86	45	20,5	119	223	2517	8,400
TB 72 H 300	72	9A	GG	291,06	289,69	-	86	45	20,5	119	270	2517	10,400
TB 84 H 300*	84	9A	GG	339,57	338,20	-	86	45	20,5	119	318	2517	12,500
TB 96 H 300*	96	9A	GG	388,08	386,71	-	86	76	5	119	366	3030	14,200
TB 120 H 300*	120	9A	GG	485,10	483,73	-	86	76	5	119	462	3030	18,800
Taper-Buchse	1108	1210	1610	1615	2012	2517	3030						
Bohrung d ₂ (mm) von... bis...	10-28	11-32	14-42	14-42	14-50	16-65	35-75						