




Ausf. 4F




Ausf. 9WF




Ausf. 9W



Ausf. 9A



Ausf. 7A



Ausf. 3A

Bezeichnung	Anzahl der Zähne	Ausführung	Material	D _p (mm)	D _e (mm)	D _f (mm)	F (mm)	S (mm)	R (mm)	D _m (mm)	D _i (mm)	Taperbuchse	Gewicht ohne Buchse (≈kg)
14M - Teilung 14 mm für Riemenbreite 40 mm													
TB 28 14M 40	28	4F	ST	124,78	122,12	128	54	32	11	-	94	2012	2,000
TB 29 14M 40	29	4F	ST	129,23	126,57	138	54	32	11	-	98	2012	2,380
TB 30 14M 40	30	4F	ST	133,69	130,99	138	54	32	11	-	98	2012	2,650
TB 32 14M 40	32	4F	ST	142,60	139,88	154	54	32	11	-	108	2012	3,400
TB 34 14M 40	34	4F	ST	151,52	148,79	160	54	45	4,5	-	110	2517	3,870
TB 36 14M 40	36	4F	ST	160,43	157,68	168	54	45	4,5	-	120	2517	4,800
TB 38 14M 40	38	4F	ST	169,34	166,60	183	54	45	4,5	-	130	2517	5,400
TB 40 14M 40	40	4F	ST	178,25	175,49	188	54	45	4,5	-	138	2517	6,000
TB 44 14M 40	44	4F	ST	196,08	193,28	211	54	51	1,5	-	155	3020	7,800
TB 48 14M 40	48	4F	ST	213,90	211,11	226	54	51	1,5	-	170	3020	9,400
TB 56 14M 40	56	9WF	ST	249,55	246,76	256	54	51	1,5	170	208	3020	10,800
TB 64 14M 40	64	9WF	GG	285,21	282,41	296	54	51	1,5	170	240	3020	13,400
TB 72 14M 40	72	9W	GG	320,86	318,06	-	54	51	1,5	170	280	3020	15,200
TB 80 14M 40	80	9A	GG	356,51	353,71	-	54	51	1,5	170	315	3020	16,000
TB 90 14M 40	90	9A	GG	401,07	398,28	-	54	51	1,5	170	360	3020	17,800
TB 112 14M 40	112	9A	GG	499,11	496,32	-	54	51	1,5	170	457	3020	25,600
TB 144 14M 40	144	9A	GG	641,71	638,92	-	54	51	1,5	170	600	3020	32,000
TB 168 14M 40	168	9A	GG	748,66	745,87	-	54	51	1,5	170	706	3020	44,000
TB 192 14M 40	192	9A	GG	855,62	852,82	-	54	51	1,5	170	813	3020	49,000
TB 216 14M 40	216	9A	GG	962,57	959,77	-	54	51	1,5	170	920	3020	55,000
14M - Teilung 14 mm für Riemenbreite 55 mm													
TB 28 14M 55	28	4F	ST	124,78	122,12	128	70	32	19	-	98	2012	2,200
TB 29 14M 55	29	4F	ST	129,23	126,57	138	70	32	19	-	100	2517	2,740
TB 30 14M 55	30	4F	ST	133,69	130,99	138	70	45	12,5	-	100	2517	2,700
TB 32 14M 55	32	4F	ST	142,60	139,88	154	70	45	12,5	-	108	2517	3,660
TB 34 14M 55	34	4F	ST	151,52	148,79	160	70	45	12,5	-	110	2517	4,550
TB 36 14M 55	36	4F	ST	160,43	157,68	168	70	45	12,5	-	120	2517	5,200
TB 38 14M 55	38	4F	ST	169,34	166,60	183	70	45	12,5	-	130	2517	6,200
TB 40 14M 55	40	4F	ST	178,25	175,49	188	70	45	12,5	-	138	2517	7,000
TB 44 14M 55	44	4F	ST	196,08	193,28	211	70	51	9,5	-	155	3020	8,600
TB 48 14M 55	48	4F	ST	213,90	211,11	226	70	51	9,5	-	170	3020	10,400
TB 56 14M 55	56	9WF	ST	249,55	246,76	256	70	51	9,5	170	208	3020	12,000
TB 64 14M 55	64	9WF	GG	285,21	282,41	296	70	51	9,5	170	242	3020	14,500
TB 72 14M 55	72	9W	GG	320,86	318,06	-	70	51	9,5	170	280	3020	16,200
TB 80 14M 55	80	9A	GG	356,51	353,71	-	70	51	9,5	170	315	3020	17,500
TB 90 14M 55	90	9A	GG	401,07	398,28	-	70	51	9,5	170	360	3020	20,100
TB 112 14M 55	112	9A	GG	499,11	496,32	-	70	51	9,5	170	457	3020	28,400
TB 144 14M 55	144	9A	GG	641,71	638,92	-	70	51	9,5	170	600	3020	36,200
TB 168 14M 55	168	9A	GG	748,66	745,87	-	70	51	9,5	170	706	3020	49,000
TB 192 14M 55	192	9A	GG	855,62	852,82	-	70	51	9,5	170	813	3020	53,000
TB 216 14M 55	216	7A	GG	962,57	959,76	-	70	89	9,5	190	920	3535	65,800
14M - Teilung 14 mm für Riemenbreite 85 mm													
TB 28 14M 85	28	4F	ST	124,78	122,12	128	102	45	28,5	-	98	2517	2,700

Bezeichnung	Anzahl der Zähne	Ausführung	Material	D _p (mm)	D _e (me)	D _f (mm)	F (mm)	S (mm)	R (mm)	D _m (mm)	D _i (mm)	Taperbuchse	Gewicht ohne Buchse (=kg)
TB 29 14M 85	29	4F	ST	129,23	126,57	138	102	45	28,5	-	100	2517	3,400
TB 30 14M 85	30	4F	ST	133,69	130,99	138	102	45	28,5	-	100	2517	3,750
TB 32 14M 85	32	4F	ST	142,60	139,88	154	102	45	28,5	-	108	2517	4,800
TB 34 14M 85	34	4F	ST	151,52	148,79	160	102	45	28,5	-	110	2517	6,000
TB 36 14M 85	36	4F	ST	160,43	157,68	168	102	51	25,5	-	120	3020	5,800
TB 38 14M 85	38	4F	ST	169,34	166,60	183	102	51	25,5	-	130	3020	6,800
TB 40 14M 85	40	4F	ST	178,25	175,49	188	102	51	25,5	-	138	3020	8,000
TB 44 14M 85	44	4F	ST	196,08	193,28	211	102	51	25,5	-	155	3030	11,800
TB 48 14M 85	48	4F	ST	213,90	211,11	226	102	51	25,5	-	170	3030	15,100
TB 56 14M 85	56	4F	ST	249,55	246,76	256	102	65	18,5	-	210	3525	19,000
TB 64 14M 85	64	9WF	GG	285,21	282,41	296	102	65	18,5	190	242	3525	23,000
TB 72 14M 85	72	9W	GG	320,86	318,06	-	102	65	18,5	190	280	3525	25,000
TB 80 14M 85	80	9A	GG	356,51	353,71	-	102	65	18,5	190	315	3525	26,000
TB 90 14M 85	90	9A	GG	401,07	398,28	-	102	65	18,5	190	360	3525	27,800
TB 112 14M 85	112	9A	GG	499,11	496,32	-	102	65	18,5	190	457	3525	36,500
TB 144 14M 85	144	9A	GG	641,71	638,92	-	102	65	18,5	190	600	3525	48,000
TB 168 14M 85	168	9A	GG	748,66	745,87	-	102	65	18,5	190	706	3525	60,000
TB 192 14M 85	192	3A	GG	855,62	852,82	-	102	102	-	190	813	4040	86,000
TB 216 14M 85	216	3A	GG	962,57	959,77	-	102	102	-	190	920	4040	91,500
14M - Teilung 14 mm für Riemenbreite 115 mm													
TB 28 14M 115	28	4F	ST	124,78	122,12	128	133	45	44	-	98	2517	3,770
TB 29 14M 115	29	4F	ST	129,23	126,57	138	133	45	44	-	100	2517	4,000
TB 30 14M 115	30	4F	ST	133,69	130,99	138	133	45	44	-	100	2517	5,000
TB 32 14M 115	32	4F	ST	142,60	139,88	154	133	45	44	-	108	2517	6,800
TB 34 14M 115	34	4F	ST	151,52	148,79	160	133	45	44	-	110	2517	6,800
TB 36 14M 115	36	4F	ST	160,43	157,68	168	133	51	41	-	120	3020	7,000
TB 38 14M 115	38	4F	ST	169,34	166,60	183	133	51	41	-	130	3020	8,400
TB 40 14M 115	40	4F	ST	178,25	175,49	188	133	51	41	-	138	3020	9,200
TB 44 14M 115	44	4F	ST	196,08	193,28	211	133	76	28,5	-	155	3030	14,000
TB 48 14M 115	48	4F	ST	213,90	211,11	226	133	76	28,5	-	170	3030	17,100
TB 56 14M 115	56	4F	ST	249,55	246,76	256	133	89	22	-	208	3535	24,800
TB 64 14M 115	64	9WF	GG	285,21	282,41	296	133	89	22	190	240	3535	27,000
TB 72 14M 115	72	9W	GG	320,86	318,06	-	133	89	22	190	280	3535	29,000
TB 80 14M 115	80	9A	GG	356,51	353,71	-	133	89	22	190	315	3535	32,000
TB 90 14M 115	90	9A	GG	401,07	398,28	-	133	89	22	190	360	3535	36,500
TB 112 14M 115	112	9A	GG	499,11	496,32	-	133	89	22	190	457	3535	46,000
TB 144 14M 115	144	9A	GG	641,71	638,92	-	133	102	15,5	230	600	4040	68,000
TB 168 14M 115	168	9A	GG	748,66	745,87	-	133	102	15,5	230	706	4040	82,600
TB 192 14M 115	192	9A	GG	855,62	852,82	-	133	102	15,5	230	813	4040	96,000
TB 216 14M 115	216	9A	GG	962,57	959,76	-	133	102	15,5	230	920	4040	107,000
14M - Teilung 14 mm für Riemenbreite 170 mm													
TB 38 14M 170*	38	4F	ST	169,34	166,60	183	187	76	55,5	-	130	3030	11,700
TB 40 14M 170*	40	4F	ST	178,25	175,49	188	187	76	55,5	-	138	3030	13,000
TB 44 14M 170*	44	4F	ST	196,08	193,28	211	187	89	49	-	153	3535	15,000
TB 48 14M 170*	48	4F	ST	213,90	211,11	226	187	89	49	-	170	3535	19,000
TB 56 14M 170*	56	4F	ST	249,55	246,76	256	187	89	49	-	208	3535	28,500
TB 64 14M 170*	64	4F	GG	285,21	282,41	296	187	102	42,5	-	240	4040	41,000
TB 72 14M 170*	72	9W	GG	320,86	318,06	-	187	102	42,5	230	280	4040	46,900
TB 80 14M 170*	80	9W	GG	356,51	353,71	-	187	102	42,5	230	315	4040	48,000
TB 90 14M 170*	90	9A	GG	401,07	398,28	-	187	102	42,5	230	360	4040	52,500

[illegible]

Taper-Buchse	2012	2517	3020	3030	3525	3535	4040	5050
Bohrung d ₂ (mm) von... bis...	14-50	16-65	25-75	35-75	35-90	35-90	40-100	70-125

GG = Grauguss ST = Stahl **Fertigungstechnische Änderungen vorbehalten.** * Keine Lagerware