




Ausf. 6F




Ausf. 6WF




Ausf. 6A



Ausf. 10WF



Ausf. 10A



Ausf. 10W

Bezeichnung	Anzahl der Zähne	Ausführung	Material	D _p (mm)	D _e (mm)	D _i (mm)	F (mm)	L (mm)	D _m (mm)	D _i (mm)	Vorbohrung d (mm)	Fertigbohrung d _{max} (mm)	Gewicht (≈kg)
14M - Teilung 14 mm für Riemenbreite 40 mm													
28 14M 40	28	6F	ST	124,78	122,12	128	54	69	100	-	24	60	4,730
29 14M 40	29	6F	ST	129,23	126,57	138	54	69	100	-	24	60	5,090
30 14M 40	30	6F	ST	133,69	130,99	138	54	69	100	-	24	60	5,450
32 14M 40	32	6F	ST	142,60	139,88	154	54	69	100	-	24	70	6,170
34 14M 40	34	6F	ST	151,52	148,79	160	54	69	100	-	24	70	6,880
36 14M 40	36	6F	ST	160,43	157,68	168	54	69	100	-	24	70	7,600
38 14M 40	38	6F	ST	169,34	166,60	183	54	69	120	-	24	70	8,280
40 14M 40	40	6F	ST	178,25	175,49	188	54	69	120	-	24	70	9,260
44 14M 40	44	6F	ST	196,08	193,28	211	54	69	120	-	24	70	10,320
48 14M 40	48	6WF	GG	213,90	211,11	226	54	69	135	170	24	70	11,500
56 14M 40	56	6WF	GG	249,55	246,76	256	54	69	135	207	28	70	13,050
64 14M 40	64	6WF	GG	285,21	282,41	296	54	69	135	240	28	70	14,400
72 14M 40	72	6A	GG	320,86	318,06	-	54	69	135	280	28	70	16,900
80 14M 40	80	6A	GG	356,51	353,71	-	54	69	135	314	28	70	18,500
90 14M 40	90	6A	GG	401,07	398,28	-	54	69	135	358	28	70	20,000
112 14M 40*	112	6A	GG	499,11	496,32	-	54	69	135	456	28	70	26,700
144 14M 40*	144	6A	GG	641,71	638,92	-	54	69	135	600	28	70	35,000
168 14M 40*	168	6A	GG	748,66	745,87	-	54	69	135	706	28	70	44,200
192 14M 40*	192	6A	GG	855,62	852,82	-	54	69	135	813	28	70	52,200
216 14M 40*	216	6A	GG	962,57	959,76	-	54	69	150	920	28	80	60,000
14M - Teilung 14 mm für Riemenbreite 55 mm													
28 14M 55	28	6F	ST	124,78	122,12	128	70	85	100	-	24	60	5,600
29 14M 55	29	6F	ST	129,23	126,57	138	70	85	100	-	24	60	6,100
30 14M 55	30	6F	ST	133,69	130,99	138	70	85	100	-	24	60	6,600
32 14M 55	32	6F	ST	142,60	139,88	154	70	85	100	-	24	70	7,600
34 14M 55	34	6F	ST	151,52	148,79	160	70	85	100	-	24	70	8,600
36 14M 55	36	6F	ST	160,43	157,68	168	70	85	100	-	24	70	9,600
38 14M 55	38	6F	ST	169,34	166,60	183	70	85	120	-	24	70	10,800
40 14M 55	40	6F	ST	178,25	175,49	188	70	85	120	-	24	70	11,200
44 14M 55	44	6F	ST	196,08	193,28	211	70	85	120	-	24	70	12,500
48 14M 55	48	10WF	GG	213,90	211,11	226	70	70	135	170	24	70	13,700
56 14M 55	56	10WF	GG	249,55	246,76	256	70	70	135	207	28	70	14,500
64 14M 55	64	10WF	GG	285,21	282,41	296	70	70	135	240	28	70	15,600
72 14M 55	72	10A	GG	320,86	318,06	-	70	70	135	280	28	70	18,500
80 14M 55	80	10A	GG	356,51	353,71	-	70	70	135	314	28	70	20,000
90 14M 55	90	10A	GG	401,07	398,28	-	70	70	135	358	28	70	22,600
112 14M 55*	112	10A	GG	499,11	496,32	-	70	70	135	456	28	70	29,500
144 14M 55*	144	10A	GG	641,71	638,92	-	70	70	135	600	28	70	39,000
168 14M 55*	168	10A	GG	748,66	745,87	-	70	70	135	706	28	70	48,500
192 14M 55*	192	10A	GG	855,62	852,82	-	70	70	135	813	28	70	57,800
216 14M 55*	216	10A	GG	962,57	959,76	-	70	70	150	920	28	80	67,000
14M - Teilung 14 mm für Riemenbreite 85 mm													
28 14M 85	28	6F	ST	124,78	122,12	128	102	202	100	-	24	60	7,700

Bezeichnung	Anzahl der Zähne	Ausführung	Material	D _p (mm)	D _e (mm)	D _i (mm)	F (mm)	L (mm)	D _m (mm)	D _i (mm)	Vorbohrung d (mm)	Fertigbohrung d _{max} (mm)	Gewicht (=kg)
29 14M 85	29	6F	ST	129,23	126,57	138	102	117	100	-	24	60	8,400
30 14M 85	30	6F	ST	133,69	130,99	138	102	117	100	-	24	60	9,100
32 14M 85	32	6F	ST	142,60	139,88	154	102	117	100	-	24	60	10,500
34 14M 85	34	6F	ST	151,52	148,79	160	102	117	100	-	24	70	11,900
36 14M 85	36	6F	ST	160,43	157,68	168	102	117	100	-	32	70	13,200
38 14M 85	38	6F	ST	169,34	166,60	183	102	117	120	-	32	70	15,150
40 14M 85	40	6F	ST	178,25	175,49	188	102	117	135	-	32	70	17,100
44 14M 85	44	6F	ST	196,08	193,28	211	102	117	135	-	32	70	23,300
48 14M 85	48	6F	ST	213,90	211,11	226	102	117	150	-	32	80	25,000
56 14M 85	56	10WF	GG	249,55	246,76	256	102	102	150	207	32	80	25,000
64 14M 85	64	10WF	GG	285,21	282,41	296	102	102	150	242	32	80	28,200
72 14M 85	72	10A	GG	320,86	318,06	-	102	102	150	278	32	80	28,800
80 14M 85	80	10A	GG	356,51	353,71	-	102	102	150	314	32	80	30,100
90 14M 85	90	10A	GG	401,07	398,28	-	102	102	150	358	32	80	33,000
112 14M 85*	112	10A	GG	499,11	496,32	-	102	102	150	456	32	80	41,800
144 14M 85*	144	10A	GG	641,71	638,92	-	102	102	150	600	32	80	52,400
168 14M 85*	168	10A	GG	748,66	745,87	-	102	102	150	706	32	80	60,300
192 14M 85*	192	10A	GG	855,62	852,82	-	102	102	165	813	32	90	70,200
216 14M 85*	216	10A	GG	962,57	959,76	-	102	102	160	920	32	90	81,000
14M - Teilung 14 mm für Riemenbreite 115 mm													
28 14M 115	28	6F	ST	124,78	122,12	128	133	148	100	-	32	60	9,200
29 14M 115	29	6F	ST	129,23	126,57	138	133	148	100	-	32	60	10,200
30 14M 115	30	6F	ST	133,69	130,99	138	133	148	100	-	32	60	11,200
32 14M 115	32	6F	ST	142,60	139,88	154	133	148	100	-	32	60	13,200
34 14M 115	34	6F	ST	151,52	148,79	160	133	148	100	-	32	70	14,800
36 14M 115	36	6F	ST	160,43	157,68	168	133	148	120	-	32	70	16,600
38 14M 115	38	6F	ST	169,34	166,60	183	133	148	120	-	32	70	19,200
40 14M 115	40	6F	ST	178,25	175,49	188	133	148	135	-	32	70	22,100
44 14M 115	44	6F	ST	196,08	193,28	211	133	148	140	-	32	80	28,000
48 14M 115	48	6F	ST	213,90	211,11	226	133	148	150	-	32	80	35,000
56 14M 115	56	6F	ST	249,55	246,76	256	133	148	150	-	32	80	44,200
64 14M 115	64	10WF	GG	285,21	282,41	296	133	133	150	240	32	80	36,800
72 14M 115	72	10A	GG	320,86	318,06	-	133	133	150	278	32	80	36,100
80 14M 115	80	10A	GG	356,51	353,71	-	133	133	150	314	32	80	38,600
90 14M 115	90	10A	GG	401,07	398,28	-	133	133	150	358	32	80	41,000
112 14M 115*	112	10A	GG	499,11	496,32	-	133	133	150	456	32	80	54,400
144 14M 115*	144	10A	GG	641,71	638,92	-	133	133	165	600	32	90	67,800
168 14M 115*	168	10A	GG	748,66	745,87	-	133	133	165	706	32	90	75,800
192 14M 115*	192	10A	GG	855,62	852,82	-	133	133	165	813	32	90	88,300
216 14M 115*	216	10A	GG	962,57	959,76	-	133	133	165	920	32	90	98,000
14M - Teilung 14 mm für Riemenbreite 170 mm													
28 14M 170*	28	6F	ST	124,78	122,12	128	187	202	100	-	32	60	13,800
29 14M 170*	29	6F	ST	129,23	126,57	138	187	202	100	-	32	60	14,200
30 14M 170*	30	6F	ST	133,69	130,99	138	187	202	100	-	32	60	15,600
32 14M 170*	32	6F	ST	142,60	139,88	154	187	202	100	-	32	60	18,100
34 14M 170*	34	6F	ST	151,52	148,79	160	187	202	100	-	32	60	20,400
36 14M 170*	36	6F	ST	160,43	157,68	168	187	202	100	-	32	70	23,500
38 14M 170*	38	6F	ST	169,34	166,60	183	187	202	120	-	32	70	26,500
40 14M 170*	40	6F	ST	178,25	175,49	188	187	202	135	-	32	85	30,100
44 14M 170*	44	6F	ST	196,08	193,28	211	187	202	140	-	32	85	37,800
48 14M 170*	48	6F	ST	213,90	211,11	226	187	202	150	-	32	85	44,500