



Bezeichnung	Anzahl der Rillen	Ausführung	Max. Bohrung	Material	D _m (mm)	D _i (mm)	F (mm)	L (mm)	R (mm)	S (mm)	Taper buchse	
8PJ												
TB 8 PJ 56	8	2	28,00	GG	-	-	23,0	23,0	-	-	1108	
TB 8 PJ 63	8	2	28,00	GG	-	-	23,0	23,0	-	-	1108	
TB 8 PJ 71	8	2	28,00	GG	-	-	23,0	23,0	-	-	1108	
TB 8 PJ 75	8	2	28,00	GG	-	-	23,0	23,0	-	-	1108	
TB 8 PJ 80	8	3	42,00	GG	70,0	-	23,0	26,0	3,0	-	1610	
TB 8 PJ 85	8	3	42,00	GG	70,0	-	23,0	26,0	3,0	-	1610	
TB 8 PJ 90	8	3	42,00	GG	70,0	-	23,0	26,0	3,0	-	1610	
TB 8 PJ 95	8	3	42,00	GG	82,0	-	23,0	26,0	3,0	-	1610	
TB 8 PJ 100	8	3	42,00	GG	82,0	-	23,0	26,0	3,0	-	1610	
TB 8 PJ 106	8	3	42,00	GG	82,0	-	23,0	26,0	3,0	-	1610	
TB 8 PJ 112	8	3	42,00	GG	90,0	-	23,0	26,0	3,0	-	1610	
TB 8 PJ 118	8	3	42,00	GG	90,0	-	23,0	26,0	3,0	-	1610	
TB 8 PJ 125	8	3	42,00	GG	90,0	-	23,0	26,0	3,0	-	1610	
TB 8 PJ 132	8	3	42,00	GG	90,0	-	23,0	26,0	3,0	-	1610	
TB 8 PJ 140	8	3	42,00	GG	90,0	-	23,0	26,0	3,0	-	1610	
TB 8 PJ 160	8	6	50,00	GG	110,0	-	23,0	32,0	4,5	4,5	2012	
TB 8 PJ 180	8	6	50,00	GG	110,0	-	23,0	32,0	4,5	4,5	2012	
TB 8 PJ 190	8	6	50,00	GG	110,0	-	23,0	32,0	4,5	4,5	2012	
TB 8 PJ 200	8	6	50,00	GG	110,0	-	23,0	32,0	4,5	4,5	2012	
TB 8 PJ 212	8	6	50,00	GG	110,0	-	23,0	32,0	4,5	4,5	2012	
TB 8 PJ 224	8	6	50,00	GG	110,0	-	23,0	32,0	4,5	4,5	2012	
TB 8 PJ 250	8	6	50,00	GG	110,0	-	23,0	32,0	4,5	4,5	2012	
TB 8 PJ 280	8	7	50,00	GG	110,0	260,0	23,0	32,0	4,5	4,5	2012	
TB 8 PJ 315	8	7	50,00	GG	110,0	295,0	23,0	32,0	4,5	4,5	2012	
12PJ												
TB 12 PJ 63	12	4	28,00	GG	-	46,0	32,5	23,0	9,5	-	1108	
TB 12 PJ 71	12	4	28,00	GG	-	46,0	32,5	23,0	9,5	-	1108	
TB 12 PJ 75	12	4	42,00	GG	-	60,0	32,5	26,0	6,5	-	1610	
TB 12 PJ 80	12	4	42,00	GG	-	60,0	32,5	26,0	6,5	-	1610	
TB 12 PJ 85	12	4	42,00	GG	-	60,0	32,5	26,0	6,5	-	1610	
TB 12 PJ 90	12	4	42,00	GG	-	74,0	32,5	26,0	6,5	-	1610	
TB 12 PJ 95	12	4	42,00	GG	-	74,0	32,5	26,0	6,5	-	1610	
TB 12 PJ 100	12	4	42,00	GG	-	74,0	32,5	26,0	6,5	-	1610	
TB 12 PJ 106	12	4	42,00	GG	-	88,0	32,5	26,0	6,5	-	1610	
TB 12 PJ 112	12	4	42,00	GG	-	88,0	32,5	26,0	6,5	-	1610	
TB 12 PJ 118	12	4	50,00	GG	-	98,0	32,5	32,0	0,5	-	2012	
TB 12 PJ 125	12	4	50,00	GG	-	98,0	32,5	32,0	0,5	-	2012	
TB 12 PJ 132	12	4	65,00	GG	-	98,0	32,5	32,0	0,5	-	2012	
TB 12 PJ 140	12	3	65,00	GG	120,0	-	32,5	45,0	12,5	-	2517	
TB 12 PJ 160	12	3	65,00	GG	120,0	-	32,5	45,0	12,5	-	2517	
TB 12 PJ 180	12	6	65,00	GG	120,0	-	32,5	45,0	6,25	6,25	2517	
TB 12 PJ 190	12	6	65,00	GG	120,0	-	32,5	45,0	6,25	6,25	2517	
TB 12 PJ 200	12	6	65,00	GG	120,0	-	32,5	45,0	6,25	6,25	2517	
TB 12 PJ 212	12	6	65,00	GG	120,0	-	32,5	45,0	6,25	6,25	2517	

Bezeichnung	Anzahl der Rillen	Ausführung	Max. Bohrung	Material	D _m (mm)	D _i (mm)	F (mm)	L (mm)	R (mm)	S (mm)	Taperbuchse	
TB 12 PJ 224	12	6	65,00	GG	120,0	-	32,5	45,0	6,25	6,25	2517	
TB 12 PJ 250	12	6	65,00	GG	120,0	-	32,5	45,0	6,25	6,25	2517	
TB 12 PJ 280	12	7	65,00	GG	120,0	260,0	32,5	45,0	6,25	6,25	2517	
TB 12 PJ 315	12	7	65,00	GG	120,0	295,0	32,5	45,0	6,25	6,25	2517	
16PJ												
TB 16 PJ 71	16	2	32,00	GG	-	55,0	42,0	42,0	-	-	1215	
TB 16 PJ 75	16	4	42,00	GG	-	60,0	42,0	26,0	16,0	-	1610	
TB 16 PJ 80	16	4	42,00	GG	-	60,0	42,0	26,0	16,0	-	1610	
TB 16 PJ 85	16	4	42,00	GG	-	60,0	42,0	26,0	16,0	-	1610	
TB 16 PJ 90	16	4	42,00	GG	-	74,0	42,0	26,0	16,0	-	1610	
TB 16 PJ 95	16	4	42,00	GG	-	74,0	42,0	26,0	16,0	-	1610	
TB 16 PJ 100	16	4	42,00	GG	-	74,0	42,0	26,0	16,0	-	1610	
TB 16 PJ 106	16	4	42,00	GG	-	88,0	42,0	26,0	16,0	-	1610	
TB 16 PJ 112	16	4	42,00	GG	-	88,0	42,0	26,0	16,0	-	1610	
TB 16 PJ 118	16	4	50,00	GG	-	98,0	42,0	32,0	10,0	-	2012	
TB 16 PJ 125	16	4	50,00	GG	-	98,0	42,0	32,0	10,0	-	2012	
TB 16 PJ 132	16	4	50,00	GG	-	98,0	42,0	32,0	10,0	-	2012	
TB 16 PJ 140	16	3	65,00	GG	120,0	-	42,0	45,0	3,0	-	2517	
TB 16 PJ 160	16	3	65,00	GG	120,0	-	42,0	45,0	3,0	-	2517	
TB 16 PJ 180	16	6	65,00	GG	120,0	-	42,0	45,0	1,5	1,5	2517	
TB 16 PJ 190	16	6	65,00	GG	120,0	-	42,0	45,0	1,5	1,5	2517	
TB 16 PJ 200	16	6	65,00	GG	120,0	-	42,0	45,0	1,5	1,5	2517	
TB 16 PJ 212	16	6	65,00	GG	120,0	-	42,0	45,0	1,5	1,5	2517	
TB 16 PJ 224	16	6	65,00	GG	120,0	-	42,0	45,0	1,5	1,5	2517	
TB 16 PJ 250	16	6	65,00	GG	120,0	-	42,0	45,0	1,5	1,5	2517	
TB 16 PJ 280	16	7	65,00	GG	120,0	260,0	42,0	45,0	1,5	1,5	2517	
TB 16 PJ 315	16	7	65,00	GG	120,0	295,0	42,0	45,0	1,5	1,5	2517	
8PL												
TB 8 PL 90	8	4	42,00	GG	-	66,0	48,0	26,0	22,0	-	1108	
TB 8 PL 95	8	4	42,00	GG	-	71,0	48,0	26,0	22,0	-	1108	
TB 8 PL 106	8	4	42,00	GG	-	82,0	48,0	26,0	22,0	-	1108	
TB 8 PL 112	8	4	42,00	GG	-	88,0	48,0	26,0	16,0	-	1610	
TB 8 PL 125	8	4	50,00	GG	-	101,0	48,0	32,0	16,0	-	1610	
TB 8 PL 132	8	4	50,00	GG	-	108,0	48,0	32,0	16,0	-	1610	
TB 8 PL 140	8	4	65,00	GG	-	116,0	48,0	45,0	3,0	-	1610	
TB 8 PL 150	8	4	65,00	GG	-	126,0	48,0	45,0	3,0	-	1610	
TB 8 PL 160	8	4	65,00	GG	-	136,0	48,0	45,0	3,0	-	1610	
TB 8 PL 170	8	4	65,00	GG	-	146,0	48,0	45,0	3,0	-	1610	
TB 8 PL 180	8	8	65,00	GG	120,0	156,0	48,0	45,0	1,5	1,5	1610	
TB 8 PL 190	8	8	65,00	GG	120,0	166,0	48,0	45,0	1,5	1,5	1610	
TB 8 PL 200	8	8	65,00	GG	120,0	176,0	48,0	45,0	1,5	1,5	2012	
TB 8 PL 212	8	8	65,00	GG	120,0	188,0	48,0	45,0	1,5	1,5	2012	
TB 8 PL 224	8	8	65,00	GG	120,0	202,0	48,0	45,0	1,5	1,5	2012	
TB 8 PL 250	8	7	75,00	GG	146,0	228,0	48,0	52,0	2,0	2,0	2012	
TB 8 PL 280	8	7	75,00	GG	146,0	256,0	48,0	52,0	2,0	2,0	2012	
TB 8 PL 315	8	7	75,00	GG	146,0	285,0	48,0	52,0	2,0	2,0	2012	
12PL												
TB 12 PL 75	12	4	32,00	GG	-	56,0	67,0	42,0	25,0	-	1215	
TB 12 PL 80	12	4	32,00	GG	-	56,0	67,0	42,0	25,0	-	1215	
TB 12 PL 85	12	4	32,00	GG	-	61,0	67,0	42,0	25,0	-	1215	
TB 12 PL 90	12	4	42,00	GG	-	66,0	67,0	42,0	25,0	-	1615	
TB 12 PL 95	12	4	42,00	GG	-	71,0	67,0	42,0	25,0	-	1615	



**optibelt RBS Keilrippenscheiben für Taper-Buchsen
Profil PL**

Bezeichnung	Anzahl der Rillen	Ausführung	Max. Bohrung	Material	D _m (mm)	D _i (mm)	F (mm)	L (mm)	R (mm)	S (mm)	Taperbuchse	
TB 12 PL 100	12	4	50,00	GG	-	79,0	67,0	32,0	35,0	-	2012	
TB 12 PL 106	12	5	50,00	GG	-	82,0	67,0	32,0	35,0	-	2012	
TB 12 PL 112	12	5	50,00	GG	-	88,0	67,0	32,0	35,0	-	2012	
TB 12 PL 125	12	5	65,00	GG	-	101,0	67,0	45,0	11,0	11,0	2517	
TB 12 PL 132	12	5	65,00	GG	-	108,0	67,0	45,0	11,0	11,0	2517	
TB 12 PL 140	12	5	65,00	GG	-	116,0	67,0	45,0	11,0	11,0	2517	
TB 12 PL 150	12	5	65,00	GG	-	126,0	67,0	45,0	11,0	11,0	2517	
TB 12 PL 160	12	5	65,00	GG	-	136,0	67,0	45,0	11,0	11,0	2517	
TB 12 PL 170	12	5	65,00	GG	-	146,0	67,0	45,0	11,0	11,0	2517	
TB 12 PL 180	12	8	65,00	GG	120,0	156,0	67,0	45,0	11,0	11,0	2517	
TB 12 PL 190	12	8	65,00	GG	120,0	166,0	67,0	45,0	11,0	11,0	2517	
TB 12 PL 200	12	8	75,00	GG	146,0	176,0	67,0	52,0	7,5	7,5	3020	
TB 12 PL 212	12	8	75,00	GG	146,0	188,0	67,0	52,0	7,5	7,5	3020	
TB 12 PL 224	12	8	75,00	GG	146,0	202,0	67,0	52,0	7,5	7,5	3020	
TB 12 PL 250	12	8	75,00	GG	146,0	228,0	67,0	52,0	7,5	7,5	3020	
TB 12 PL 280	12	8	75,00	GG	146,0	256,0	67,0	52,0	7,5	7,5	3020	
16PL												
TB 16 PL 85	16	5	32,00	GG	-	61,0	86,0	42,0	22,0	22,0	1215	
TB 16 PL 90	16	5	42,00	GG	-	66,0	86,0	42,0	22,0	22,0	1615	
TB 16 PL 95	16	5	42,00	GG	-	71,0	86,0	42,0	22,0	22,0	1615	
TB 16 PL 100	16	5	50,00	GG	-	79,0	86,0	32,0	27,0	27,0	2012	
TB 16 PL 106	16	5	50,00	GG	-	82,0	86,0	32,0	27,0	27,0	2012	
TB 16 PL 112	16	5	50,00	GG	-	88,0	86,0	32,0	27,0	27,0	2012	
TB 16 PL 125	16	5	65,00	GG	-	101,0	86,0	45,0	20,5	20,5	2517	
TB 16 PL 132	16	5	65,00	GG	-	108,0	86,0	45,0	20,5	20,5	2517	
TB 16 PL 140	16	5	65,00	GG	-	116,0	86,0	45,0	20,5	20,5	2517	
TB 16 PL 150	16	5	65,00	GG	-	126,0	86,0	45,0	20,5	20,5	2517	
TB 16 PL 160	16	5	75,00	GG	-	136,0	86,0	52,0	17,0	17,0	3020	
TB 16 PL 170	16	5	75,00	GG	-	146,0	86,0	52,0	17,0	17,0	3020	
TB 16 PL 180	16	5	75,00	GG	-	156,0	86,0	52,0	17,0	17,0	3020	
TB 16 PL 190	16	8	75,00	GG	146,0	166,0	86,0	52,0	17,0	17,0	3020	
TB 16 PL 200	16	8	75,00	GG	146,0	176,0	86,0	52,0	17,0	17,0	3020	
TB 16 PL 212	16	8	75,00	GG	146,0	188,0	86,0	52,0	17,0	17,0	3020	
TB 16 PL 224	16	8	75,00	GG	146,0	202,0	86,0	52,0	17,0	17,0	3020	
TB 16 PL 250	16	7	90,00	GG	178,0	228,0	86,0	89,0	1,5	1,5	3535	
TB 16 PL 280	16	7	90,00	GG	178,0	256,0	86,0	89,0	1,5	1,5	3535	
TB 16 PL 315	16	7	90,00	GG	178,0	285,0	86,0	89,0	1,5	1,5	3535	

